

Reliable pH documentation...

... with the inoLab [®] pH 7310

The new inoLab [®] pH 7310 is the ideal instrument for precision measurements and automatic documentation complying with GLP/AQS in quality laboratories throughout all industries. Optional built-in printer available on demand.

inoLab [®] pH 7310

- USB interface for fast data transfer
- Data output in .csv format or via optional built-in printer
- CMC-function for monitoring the measuring range

Measuring reliability

- Repeatable measuring results provided by the active, automatic AutoRead function with recognition of stable end values
- The CMC function visualizes the optimal measuring range and supports correct measuring
- Graphic display with plain text menu for convenient and secure operation

GLP/AQA documentation

- Alphanumeric entry of electrode serial number
- Transfer of all data in .csv format via USB interface to PC, on demand formatted transfer into Excel (MultiLab [®] Importer, included in the delivery scope or as download).
- Data output via optional built-in printer possible



Flexible and powerful:

- 1- to 5-point calibration with calibration timer for all measuring duties
- 22 stored buffer sets for easy calibration
- 1- to 5-point calibration with customized buffers
- Backlit graphic display with CMC

KEF

PROMOCIJA

INOLABR PH 7310 SET 4

*1050€ SET!



Technical Data			
Model	inoLab [®] pH 7310		
Range/ Resolution	pH	-2.0 ... 20.0 ±0.1 pH -2.00 ... 20.00 ±0.01 pH -2.000 ... 19.999 ±0.005 pH	
	mV Temperature	±(1200.0 ±0.3) mV ±(2500 ±1) mV	
Accuracy (±1 digit)	pH	±0.005 pH ±0.01 pH	
	mV Temperature	±0.3 mV, ±1 mV ±0.1 K	
Calibration	1, 2, 3, 4, 5-point calibration WTW technical buffers, DIN/NIST buffers plus 20 additional buffer sets		
inoLab [®] Labor-pH-Meter SETs □ Order No. ▲ Order No.			
inoLab [®] pH 7310 SET 4	Convenient, menu controlled pH/mV benchtop meter for measurements/documentation according GLP/AQA. Set including combined pH electrode. Meter with universal power supply, stand and operation manual. Combined pH electrode SenTix [®] 81, buffer 4, 7 and 10.01, 3 mol/l KCl, software and USB cable.		na 1AA314



□ with BNC plug ▲ with DIN plug

For other SETs or electrodes in SET, see WTW Product Details

Parameter

Multi-parameter

pH

ORP

ISE

Dissolved Oxygen (D.O.)

Conductivity

Data logger/flow + level

BOD/Respiration

Photometers

Turbidity

Colony Counter

Software/Printers